

## ENERGY EFFICIENCY

Thermal Transmission Coefficient  
 **$U_w$  from 1.1 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## ACCUSTIC INSULATION

Maximum glazing: **45 mm.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class 9A**

Wind resistance (UNE-EN 12210:2000):

**Class A3**

Reference test: 2,700 x 2,530 mm. 3 sashes

Security test (PAS 24:2012):

**Complies**

Reference test: 3 sashes. Configuration 330. 2,701 x 2,517 mm.

|                            |   |                               |   |
|----------------------------|---|-------------------------------|---|
| <b>SECTIONS</b>            | Frame 73 mm<br>Sash 73 mm   | <b>EXTRUSION ALLOY</b>        | 6063 T-5  |
| <b>PROFILE THICKNESS</b>   | Door 1.8 mm   | <b>POLYAMIDE STRIP LENGTH</b> | Polyamide 6.6 reinforced with 25% fiberglass:<br>Frame 20 mm Sash 30 mm |
| <b>MAXIMUM DIMENSIONS</b>  | Width (L) = 1,200 mm<br>Height (H) = 3,000 mm   | <b>OPENING POSIBILITIES</b>   | Bi-fold up to 14 sashes<br>Possibility of corner opening at 90°         |
| <b>MAXIMUM WEIGHT/SASH</b> | 120 Kg.   | <b>ACCESSIBILITY</b>          | Possibility of embedded low threshold                                   |
| <b>FINISHES</b>            | Colour powder coating (RAL, mottled, rough...)<br>According to Qualicoat >60 microns<br>Wood effect powder coating<br>According to Qualideco standard<br>Anodized<br>According to Ewwa Euras Standard Class 15<br>Optionally Class 20 and 25<br>Optionally bicoloured |                               |   |

Please consult regarding maximum weight and dimensions according to types

